




P1000®




DF GR HG PG PI



Ww/100 Ft: 189 Lbs (281 kg/100 m)  
 Allowable Moment 5,070 In-Lbs (570 N-m)  
 12 Gauge Nominal Thickness .105" (2.7mm)

P1001

DF GR HG PG PI




Ww/100 Ft: 378 Lbs (562 kg/100 m)  
 Allowable Moment 14,360 In-Lbs (1,620 N-m)  
 12 Gauge Nominal Thickness .105" (2.7mm)

P1000 DS

P1000 H3 GR HG PG PI

P1000 HS GR HG PG PI

P1000 KO GR PG



Ww/100 Ft: 173 Lbs (257 kg/100 m)

Ww/100 Ft: 175 Lbs (260 kg/100 m)




Ww/100 Ft: 190 Lbs (283 kg/100 m)

Ww/100 Ft: 185 Lbs (275 kg/100 m)

P1000 SI GR HG PG PI

P1000 T DF GR HG PG PI

P1000 WT DF GR HG PG PI



Ww/100 Ft: 185 Lbs (275 kg/100 m)

Ww/100 Ft: 185 Lbs (275 kg/100 m)

Ww/100 Ft: 185 Lbs (275 kg/100 m)

CHANNEL NUTS



Channel Finishes: DF, PL, GR, HG, PG, ZD; Standard Lengths: 10' & 20'

1 1/2" System  
 Telestrut  
 Nuts & Hardware  
 General Fittings  
 Pipe/Conduit Support  
 Concrete Inserts  
 Solar  
 1 1/4" System  
 3/4" System  
 Special Metals