



P1045




Wt/100 pcs: 55 Lbs (24.9 kg)

P1479A THRU P1479E




Part Number	"A" In (mm)	Wt/100 pcs Lbs (kg)
P1479A	4 (101.6)	81 (36.7)
P1479B	5 (127.0)	92 (41.7)
P1479C	6 (152.4)	104 (47.2)
P1479D	7 (177.8)	115 (52.2)
P1479E	8 (203.2)	127 (57.6)

P1347




Wt/100 pcs: 55 Lbs (24.9 kg)

P1730




Wt/100 pcs: 54 Lbs (24.5 kg)

P1453




Wt/100 pcs: 70 Lbs (31.8 kg)

P1734




Wt/100 pcs: 70 Lbs (31.8 kg)

P1454




Wt/100 pcs: 38 Lbs (17.2 kg)

P1736




Wt/100 pcs: 70 Lbs (31.8 kg)

P2360




Wt/100 pcs: 9 Lbs (4.1 kg)

P3345




Wt/100 pcs: 47 Lbs (21.3 kg)

P5560




Wt/100 pcs: 11 Lbs (5.0 kg)

P4045




Wt/100 pcs: 47 Lbs (21.3 kg)

P3045




Wt/100 pcs: 53 Lbs (24.0 kg)

P5545




Wt/100 pcs: 67 Lbs (30.4 kg)

P612



Wt/100 pcs: 47 Lbs (21.3 kg)

P2469




Wt/100 pcs: 93 Lbs (42.2 kg)

Standard Dimensions for 1 1/8" (41.3mm) width series channel fittings (Unless Otherwise Shown on Drawing)


Hole Diameter: 5/16" (14.3mm); Hole Spacing - From End: 1 1/8" (20.6mm); Hole Spacing - On Center: 1 1/2" (47.6mm); Width: 1 1/8" (41.3mm); Thickness: 1/4" (6.4mm) with steel meeting or exceeding ASTM A1011 SS GR 33, or 0.220" (5.6mm) with steel meeting or exceeding ASTM A1011 HSLAS GR 45

P6332




Wt/100 pcs: 19 Lbs (8.6 kg)

P6546




Wt/100 pcs: 8 Lbs (3.6 kg)

P6045




Wt/100 pcs: 7 Lbs (3.2 kg)

P6186




Wt/100 pcs: 8 Lbs (3.6 kg)

P6454




Wt/100 pcs: 5 Lbs (2.3 kg)

P7045




Wt/100 pcs: 6 Lbs (2.7 kg)

P6453




Wt/100 pcs: 9 Lbs (4.1 kg)

P6047, P7047




Part No.	A In (mm)	Wt/100 pcs Lbs (kg)	Use with Channel
P6047	13/16 20.6	12 5.4	P6000
P7047	13/32 10.3	10 4.5	P7000

P6737




Wt/100 pcs: 16 Lbs (7.3 kg)

P6048




Wt/100 pcs: 14 Lbs (6.4 kg)

P6376




Wt/100 pcs: 17 Lbs (7.7 kg)

P7376




Wt/100 pcs: 11 Lbs (5.0 kg)

P6376A




Wt/100 pcs: 26 Lbs (11.8 kg)

P7376A




Wt/100 pcs: 16 Lbs (7.3 kg)

P6377



Wt/100 pcs: 36 Lbs (16.3 kg)

P7377



Wt/100 pcs: 24 Lbs (10.9 kg)

Standard Dimensions for 13/16" (20.6mm) width series channel fittings (Unless Otherwise Shown on Drawing)

Hole Diameter: 1/2" (7.1mm); Hole Spacing - From End: 13/32" (10.3mm); Hole Spacing - On Center: 1 1/8" (27.0mm); Width: 13/16" (20.6mm); Thickness: 1/8" (3.2mm)